



REFRIGERATED MINCERS



DRC CR82 and CR22

Model	size (mm)	Packaging (mm)	Weight (kg)	Theoretical output (kg/h)	Motor power	Voltage
DRC CR 82	482 x 363 x 579	670 x 480 x 705	45	300	1.5 HP 1.1 kW	3/380 V
DRC CR 22						

GENERAL FEATURES

- CR82 - Unger H82 (delivered with 3 mm plate)
- CR22 - Enterprise N22 (Delivered with 3 mm plate)

OPTION

- Single phase motor



DRC CR82 With burger former

Model	size (mm)	Packaging (mm)	Weight (kg)	Theoretical output (kg/h)	Motor power	Voltage
DRC CR 82	521 x 505 x 579	670 x 480 x 705	45	300	1.5 HP 1.1 kW	3/380 V

GENERAL FEATURES

- CR82 - Unger H82 (delivered with 3 mm plate)
- Multicalibre oval burger former from 100g to 200g (Allows you to vary the diameter of your steaks)
- or
- Monocalibre round burger former (Thickness 18 mm) : Ø83 (100g); Ø90 (120g); Ø100 (150g); Ø110 (170g); Ø120 (200g)

OPTION

- Single phase motor



DRC CR82 and CR22 multi

With single round shape former, Variable thickness

Model	size (mm)	Packaging (mm)	Weight (kg)	Theoretical output (kg/h)	Motor power	Voltage
DRC CR 82	647 x 444 x 579	670 x 720 x 705	50	300	1.5 HP 1.1 kW	3/380 V
DRC CR 22						

GENERAL FEATURES

- CR82 - Unger H82 (delivered with 3 mm plate)
- CR22 - Enterprise N22 (Delivered with 3 mm plate)
- Single 100 mm diameter, from 12 to 24 mm thickness (100g to 200g) (Allows you to vary the thickness of your steaks from 12 to 24 mm)

OPTION

- Single phase motor



DRC VR82 With burger former

Model	size (mm)	Packaging (mm)	Weight (kg)	Theoretical output (kg/h)	Motor power	Voltage
DRC VR82	526 x 526 x 579	900 x 720 x 705	60	300	1.5 HP 1.1 kW	3/380 V

GENERAL FEATURES

- VR82 - Unger H82 (delivered with 3 mm plate)
- Lightened plexi-door
- Safety switch on plexi-door
- Multicalibre oval burger former from 100g to 200g (Allows you to vary the diameter of your steaks)
- or
- Monocalibre round burger former (Thickness 18 mm) : Ø83 (100g); Ø90 (120g); Ø100 (150g); Ø110 (170g); Ø120 (200g)

OPTION

- Single phase motor

REFRIGERATED MINCERS



DRC R98 and R32

Model	size (mm)	Packaging (mm)	Weight (kg)	Theoretical output (kg/h)	Motor power	Voltage
DRC R98	550 x 437 x 630	900 x 720 x 705	71	600	3 HP 2.2 kW	3/380 V
DRC R32	510 x 437 x 630					

GENERAL FEATURES

- R98 - Unger B98 (delivered with 5 mm plate)
- R32 - Enterprise N32 (delivered with 5 mm plate)

OPTION

- Single phase motor



DRC R98 and R32 With burger former

Model	size (mm)	Packaging (mm)	Weight (kg)	Theoretical output (kg/h)	Motor power	Voltage
DRC R98 REC	580 x 437 x 630	900 x 720 x 705	71	600	3 HP 2.2 kW	3/380 V

GENERAL FEATURES

- R98 - Unger B98 (delivered with 5 mm plate)
- Multicalibre oval burger former from 100g to 200g (Allows you to vary the diameter of your burgers)
- or
- Monocalibre round burger former (Thickness 18 mm) : Ø83 (100g); Ø90 (120g); Ø100 (150g); Ø110 (170g); Ø120 (200g)

OPTION

- Single phase motor

Non-contractual photos

BURGER FORMER



Spare former (For machines originally equipped with burger former)

- Multicalibre oval burger former from 100g to 200g (Allows you to vary the diameter of your burgers)
- Monocalibre round burger former (Thickness 18 mm) : Ø83 (100g); Ø90 (120g); Ø100 (150g); Ø110 (170g); Ø120 (200g)

